

IN THE CLAIMS

Please amend the claims as indicated below:

- 5 1. (Previously Presented) An optical receiving unit for a wireless communications link,
said optical receiving unit comprising:
 a receiving unit including at least one objective optic element; and
 an optical bundle operable to receive an optical communication signal, wherein said
optical bundle is comprised of an array of optical fibers arranged surrounding a receiving fiber,
10 wherein an intensity of said optical communication signal received by said receiving fiber relative to
an intensity of said optical communication signal received by said array of optical fibers is used to
adjust an orientation of said receiving unit.
- 15 2. (Original) The optical receiving unit of claim 1, wherein said array is comprised of N
fibers and wherein N is selected to facilitate fabrication of said optical bundle.
3. (Original) The optical receiving unit of claim 1, wherein a core diameter and
numerical aperture of said array of optical fibers are selected to capture as much light as possible.
- 20 4. (Original) The optical receiving unit of claim 1, wherein said receiving fiber is
recessed relative to said array.
5. (Original) The optical receiving unit of claim 4, wherein said receiving fiber is
recessed relative to said array by appending an extension bundle to said optical bundle to add
25 additional length to each of said fibers in said array.
6. (Original) The optical receiving unit of claim 5, wherein said extension bundle is
comprised of an array of fibers arranged around a central fiber and said central fiber is then removed
from the extension bundle.

7. (Original) The optical receiving unit of claim 4, wherein said receiving fiber is recessed relative to said array by appending a silica disk to said optical bundle.

5 8. (Original) The optical receiving unit of claim 7, wherein said silica disk has a hole in the center and wherein an outer diameter of said silica disk is at least equal to the diameter of said optical bundle and an inner diameter of said silica disk is approximately equal to the core diameter of said receiving fiber.

10 9. (Currently Amended) An optical receiving unit for a wireless communications link, said optical receiving unit comprising:

a receiving unit including at least one objective optic element; and

an optical bundle operable to receive an optical signal, wherein said optical bundle is comprised of an array of optical fibers arranged surrounding a receiving fiber, wherein said array of
15 optical fibers detects a location of said signal relative to said receiving fiber and provides feedback to adjust an orientation of said receiving unit based on an intensity of said optical communication signal received by said receiving fiber relative to an intensity of said optical communication signal received by said array of optical fibers.

20 10. (Original) The optical receiving unit of claim 9, wherein said array is comprised of N fibers and wherein N is selected to facilitate fabrication of said optical bundle.

11. (Original) The optical receiving unit of claim 9, wherein a core diameter and numerical aperture of said array of optical fibers are selected to capture as much light as possible.

25 12. (Original) The optical receiving unit of claim 9, wherein said receiving fiber is recessed relative to said array.

13. (Original) The optical receiving unit of claim 12, wherein said receiving fiber is

recessed relative to said array by appending an extension bundle to said optical bundle to add additional length to each of said fibers in said array.

14. (Original) The optical receiving unit of claim 13, wherein said extension bundle is
5 comprised of an array of fibers arranged around a central fiber and said central fiber is then removed from the extension bundle.

15. (Original) The optical receiving unit of claim 12, wherein said receiving fiber is
10 recessed relative to said array by appending a silica disk to said optical bundle.

16. (Original) The optical receiving unit of claim 15, wherein said silica disk has a hole
in the center and wherein an outer diameter of said silica disk is at least equal to the diameter of said
optical bundle and an inner diameter of said silica disk is approximately equal to the core diameter
of said receiving fiber.

17. (Original) A method of aligning an optical receiving unit with an optical transmitting
unit in a wireless communications link, said method comprising:

receiving an optical signal using an optical bundle comprised of an array of optical
fibers arranged surrounding a receiving fiber;

20 measuring a signal strength of said optical signal in each fiber in said array of optical
fibers and in said receiving fiber; and

repositioning said optical bundle to reduce the signal strength in said fibers in said
array of optical fibers and to increase the signal strength in said receiving fiber.

25 18. (Original) The method of claim 17, further comprising the step of recessing said
receiving fiber relative to said array.

19. (Original) The method of claim 18, further comprising the step of appending an
extension bundle to said optical bundle to add additional length to each of said fibers in said array.

20. (Original) The method of claim 18, further comprising the step of appending a silica disk to said optical bundle.